



TEMPERATURE CONTROLLED UNITS



Standard features include:

- Fully lockable butcher's door with internal emergency door release mechanism
- Man-trapped alarm
- Tamper-free lockable controls
- Aluminium chequer-plate flooring
- Interior lighting IP65
- Emergency lighting
- Temperature range +25°C to -25°C

Power requirements:

- 415 volt, A.C., 50 Hz
- 32 amp, five-wire circuit
- Three-phase power with earth and neutral required
- 32 amp circuit breaker type 'D' motor start
- A 32 amp outlet socket needs to be within 10m of the unit machinery. This should be protected with an residual circuit breaker overload (RCBO)
- Please ensure you have a plug that fits your 32 amp socket
- The maximum power draw for the 20ft in an ambient temperature of 25°C, is 6kWh. When set point is reached, the unit will start cycling and the total power draw will fall to approx 3kWh. Note that this will vary depending on door openings, cargo and ambient temperatures
- The maximum power draw for the 40ft in an ambient temperature of 25°C, is 8kWh. When set point is reached the unit will start cycling and the total power draw will fall to approx 4kWh. Note that this will vary depending on door openings, cargo and ambient temperatures

TEMPERATURE CONTROLLED

Butcher Door Units 20ft & 40ft

The Spacewise standard Butcher Door unit is designed to take care of ALL your temperature controlled storage needs. Our refrigerated units are fully insulated with stainless steel interiors, the refrigeration machinery is integral to the unit and has an operating temperature range of -25° C to +25° C.

Each unit has an easy access "Butchers Door" which is lockable for added security and can be fitted with an optional aluminium ramp for easy access when loading with Pallet trucks or roll cages.

This product complies with current health & safety regulations and is fitted with an internal emergency door release along with a push button panic alarm system which when activated has an audible alarm with an external warning light.

Fitted as standard every unit has interior lighting to IP65 standard, external lighting for 24 hour access and safe loading and unloading of contents. An aluminium checker plate floor provides a safe hygienic and easy to clean surface.

Dimensions (mm)	20ft (6.1m)	40ft (12.2m)
External		
Length	6,058	12,192
Width	2,438	2,438
Height	2,591	2,591
Internal		
Usable length	4,300	10,400
Length	5,566	11,620
Width	2,269	2,294
Height	2,253	2,230
Openings		
Width	2,271	2,271
Height	2,182	2,182
Butcher's door opening	1,800 x 2,000 (clear opening)	1,800 x 2,000 (clear opening)
Capacity		
Usable Internal c.c.	22cu m	54cu m
Pallet Euro 1,200 x 800	8	21
Pallet Metric 1,200 x 1,000mm	7	18

Optional extras:

- Aluminium Ramp 2000L x 1200W
- Low Noise Units
- Extra High Units
- Side Door Access
- Spacewise remote monitoring system



Fortis House, 160 London Road, Barking, Essex IG11 8BB UK
T: 0800 132 981 F: +44 (0)20 8214 1316
E: spacewise@talinternational.com W: www.spacewise.co.uk

Actual measurements and other specification details may vary from those shown due to Spacewise's policy of constant product development. Spacewise is the trading name of ICS Terminals (UK) Ltd.