

## LAUNCHING OUR NEW ROCKET

PREMIUM QUALITY SILICONE SEALANT

AVAILABLE IN

CLEAR & WHITE 300ml

BUY 300ml TUBE

1+ £2.40

25+ £2.00

75+ **£1.80** 

CLEAR - 5120000

WHITE - 5120010



ONLY AVAILABLE
FROM ORBITAL
FASTENERS LTD



## ROCKET PREMIUM QUALITY SILICONE SEALANT



## **ADVANTAGES:**

- Neutral oxime curing, 1-component silicone sealant (RTV-1)
- Has a high resistance to ageing, weather conditions, UV & chemical products
- Excellent adhesion to almost all building materials
- Very easy to apply
- Permanent elasticity

## **APPLICATIONS:**

- Has an adhesive strength without primer on the majority of materials used in building and engineering industries such as treated wood, aluminium, steel, abs, stainless steel, anodised steel, PVC, etc.
- Appropriate for placing laminated glass (does not affect the layer PVB)
   & double glass (does not affect the butyl sealing)
- Can also be used on alkali surfaces such as concrete, bricks. A primer is recommended.

| TECHNICAL CHARACTERISTICS  |                             |
|--|-----------------------------|
| Uncured sealant  |                             |
| Type of sealant  | Polysiloxanes               |
| Viscosity  | Pasty                       |
| Vulcanising system   | Through moisture in the air |
| Skin forming time (23°C and 50% R.H.)                                      | 25 min                      |
| Vulcanisation rate (23°C and 50% R.H.)                                     | 2,5 - 3 mm/24h              |
| Density : ISO 1183   | 1,36 g/ml                   |
| Processing temperature   | +5°C - +40°C                |
| Shelf life, in the original packing in dry conditions between +5°C - +25°C | Min. 12 months              |
| Cured sealant  |                             |
| Shore A hardness : ISO 868   | 20                          |
| Elastic recovery : ISO 7389  | >90%                        |
| Deformation capability : ISO 11600   | 25%                         |
| Modulus at 100% elongation : ISO 8339                                      | 0,36 N/mm <sup>2</sup>      |
| % Elongation at break : ISO 8339   | 260%                        |
| voc  | < 100 g/l                   |
| Temperature resistance   | -50°C - +150°C              |

0074
16
Orbital Fasteners
EN 15651-1
F EXT-INT
EN 1561-2

FOR MORE INFORMATION ASK A MEMBER OF STAFF

Call **01923 777 777** 

Click www.orbitalasteners.co.uk

Email sales@orbitalfasteners.co.uk

Visit

Olds Approach, Tolpits Lane Watford, WD18 9XT

BUY 300ml TUBE 1+ £2.40 25+ £2.00

75+ **£1.80** 

CLEAR - 5120000

WHITE - 5120010





ONLY AVAILABLE FROM ORBITAL FASTENERS LTD