

ALTO Room Scaffold

ISSUE 01	DATE Nov 15	PAGE 1 of 2
-----------------	--------------------	--------------------

Overview

The Alto Room Scaffold is designed to put operatives safely at height at lower levels than the Alto MD Ladderspan Tower, whilst incorporating a compact design, and less component pieces. Ideal for end-user ownership or part of a hire fleet, the Alto Room Scaffold is perfect for indoor height access or use on level outdoor areas. Highly portable and manoeuvrable, this two-man mini tower provides platform working heights of up to 1.75m. The Alto Room Scaffold also possesses the same loading capacity of the Alto MD tower.

As with all Alto Tower products, the Alto Room Scaffold is manufactured from durable 48mm dia. extruded aluminium tube. Using the 2mm thick Alto MD tube, durability, strength and rigidity come as standard. Compact stabilisers & double-braked castor wheels provide the usual safe operating environment that our customers expect from the Alto Tower range.

Specification

TOWER STANDARD	BS 1139-6:2014
PLATFORM LENGTHS	1.6m long & 2.4m long
TOWER WIDTH	0.74m wide
PLATFORM HEIGHTS	0.41m, 0.66m, 0.91m, 1.16m, 1.41m & 1.66m
TOWER LOADING	1.6m = 186 kg 2.4m = 282 kg
TUBE THICKNESS	2.0mm extruded aluminium 6082T6 fluted tube
TUBE DIAMETER	48mm diameter tube (standard scaffold tube dia.)



Lakeside Industries Ltd

Unit 19 Howard Road, Park Farm Industrial Estate, Redditch, Worcestershire. B98 7SE
 +44(0)1527 500577 | sales@lakeside-industries.co.uk | www.lakeside-industries.co.uk

ALTO Room Scaffold

ISSUE 01	DATE Nov 15	PAGE 2 of 2
-----------------	--------------------	--------------------

Key Features

2mm Thick Wall Tube

Means wear & tear damage is significantly reduced because it is more resistant to denting and crushing than the Lightweight alternatives.

Unique Fluted Tube

Makes identification & segregation of the Alto MD Products easier. The ribbed design also gives enhanced strength to the tube profile.

Compact Folding Frame

The main framework of the tower is one single item that can be rapidly deployed. The folded frame is highly manoeuvrable and fits through and standard door.

Standard Alto Parts

The Alto Room Scaffold uses standard MD platforms, braces and toeboards. This makes for efficient utilisation in hire fleets when combined with the standard MD Tower range.

Two-man Capacity

As the Alto Room Scaffolds use standard MD components, both the 1.6m and 2.4m long versions have the capacity to take 2 operatives at the same time.