

Lumberg has extended its existing Quicklock connectivity range now by an even more powerful version in size M28, available in 2-pole, 3-pole and 8-pole, gold plated contacts. The 2-pole and 3-pole is with screw clamps whereas the 8-pole is a solder version. Available in cable and chassis mount options.

The IP67 rated, easy mating connectors are a robust solution for industrial applications where higher rating up to 50 Amps are required. The connectors are already available through our distributor network such as RS, Farnell and Easby Electronics are listing the parts as we speak.



Details related to the images above.

***New Quicklock Plug (Male)**

Part Number	Number of Poles	Connector Size	Rated Current	Connector Housing	Locking Latch
0254 02	2	M28	50A	PBT, V-0 acc. to UL94	YES
0254 03	3	M28	43A	PBT, V-0 acc. to UL94	YES
0254 08	8	M28	17A	PBT, V-0 acc. to UL94	YES
025528 02	2	M28	50A	PBT, V-0 acc. to UL94	-
025528 03	3	M28	43A	PBT, V-0 acc. to UL94	-

***New Quicklock Flange Chassis Plug (Male)**

Part Number	Number of Poles	Connector Size	Rated Current	Connector Housing	Locking Latch
024028 02	2	M28	50A	Zn alloy, chrome-plated	-

024028 03	3	M28	43A	Zn alloy, chrome-plated	-
-----------	---	-----	-----	-------------------------	---

***New Quicklock Socket (Female)**

Part Number	Number of Poles	Connector Size	Rated Current	Connector Housing	Locking Latch
0264 02	2	M28	50A	PBT, V-0 acc. to UL94	-
0264 03	3	M28	43A	PBT, V-0 acc. to UL94	-
026528 02	2	M28	50A	PBT, V-0 acc. to UL94	YES
026528 03	3	M28	43A	PBT, V-0 acc. to UL94	YES

***New Quicklock Flange Chassis Socket (Female)**

Part Number	Number of Poles	Connector Size	Rated Current	Connector Housing	Locking Latch
0274 02	2	M28	50A	Zn alloy, chrome-plated	-
0274 03	3	M28	43A	Zn alloy, chrome-plated	-
0274 08	8	M28	17A	Zn alloy, chrome-plated	-